

- ✓ Reduce fire risk > Flash point at 30 ° C / 86 ° F
- ✓ Improve working conditions > Soft odor
- ✓ Reduce consumption up to 60 % > Lower evaporation rate
- ✓ Reduce environmental impact > Lower VOC emissions & waste
- ✓ No occupational exposure limit



## A MULTI-PURPOSE CLEANING SOLVENT

A multi-purpose, powerful solvent cleaner with controlled volatility for surface preparation operations prior to painting, bonding and sealing applications.



	Acetone	DIESTONE DLS
Hazard statements	H225 - Highly flammable liquid and vapor. H319 - Causes serious eye irritation. H336 - May cause drowsiness or dizziness.	H226 - Flammable liquid and vapour. H336 - May cause drowsiness or dizziness.
Flash point	-17 ° C / 1,4 ° F	30 ° C / 86 ° F
VOC	100 % VOC	100 % VOC
Evaporation rate (n-Butyl acetate)	7.7	0.5
Vapor pressure (mmHg at 20 ° C)	184.5	9.3
Specific gravity value (kg/m3)	792	900
Cleaner odor	strong	soft
Exposure limite value	500 ppm (1210 mg/m3)	N/A



# A "ONE FOR ONE" PRODUCT REPLACEMENT

## > CLEANING EFFICIENCY

Pollutants	Acetone	DIESTONE DLS
	on aluminium / carbon fiber	on aluminium / carbon fiber
Grease	✓	✓
Oil	✓	✓
Dust	✓	✓
Un-cured Resine / Sealant	✓	✓
Semi-cured Resine / Sealant	✓	✓

## > APPROVED OPERATIONS

	Acetone	DIESTONE DLS
	Degreasing	✓
General degreasing	✓	✓
Wet/Uncured sealant & adhesive removal	✓	✓
Surface preparation before bonding & sealing	✓	✓
Cleaning before painting	✓	✓

## ALSO AVAILABLE IN PRE-SATURATED FORM FOR FURTHER COST REDUCTIONS

### ELIMINATE BULK LIQUIDS



- Eliminate manual saturation process
- Standardize cleaning operations
- Reduce consumption



- Improve quality & production performance
- Reduce cleaning time
- Reduce VOC emissions, waste & environmental impact
- Improve working conditions - no risk of slips, falls or fires
- Eliminate hazardous liquid transport, storage & logistics



### REDUCE OPERATIONAL COSTS

